



NOTE: INSTALL ALL WIRING PER LOCAL CODE.

LEGEND

1. WEATHERTRAK ET PRO² SWM SMART WATER MANAGER SERIES CONTROLLER WITHIN VANDAL RESISTANT POWDER COATED COLD ROLLED STEEL WALL MOUNT ENCLOSURE ASSEMBLY W/KEY-LOCK. SEE SPECIFICATIONS FOR SIZE AND FINISH.
2. #6 COPPER GROUND WIRE IN CONDUIT. CONNECT TO BUILDING GROUND AS REQUIRED BY NATIONAL AND LOCAL ELECTRICAL CODES.
3. 1-1/2" PVC SCH. 40 CONTROL WIRE CONDUIT.
4. FLOOR WITHIN CONTROLLER EQUIPMENT ROOM.
5. 1-1/2" PVC LONG SWEEP ELL AND CONDUIT. EXTEND UNDER FLOOR TO PLANTING AREA - SIZE AS REQUIRED.
6. LOW VOLTAGE CONTROL WIRING FROM AUTOMATIC CONTROLLER TO ELECTRIC CONTROL VALVES.
7. WALL SURFACE. ANCHOR CONTROLLER TO WALL PER MANUFACTURER'S RECOMMENDATIONS.
8. "J" BOX FOR 120 VOLT CONNECTION TO CONTROLLER TRANSFORMER.
9. LOW PROFILE ANTENNA.
10. CONTROLLER TRANSFORMER.
11. WIRED OR WIRELESS RAIN SENSOR PER SPECS. LOCATE SENSOR OUTSIDE PER MANUFACTURER'S RECOMMENDATION. FOR WIRED SENSOR, WIRE BACK TO CONTROLLER.
12. 3/4" PVC SWEEP ELL AND CONDUIT FOR FLOW SENSOR CABLE AND MASTER VALVE WIRES.
13. FLOW SENSOR CABLE AND MASTR VALVE WIRES PER SPECIFICATIONS.

WALL MOUNT INDOOR INSTALLATION FOR

WeatherTRAK ET PRO² SWM

SCALE: N.T.S.

